

Welcome to the best Mini yet







Clubman Saloon

The Mini Clubman Saloon really looks a special kind of Mini. With extra performance, extra features, with its distinctive bonnet, coachline and wheel trims, the Mini Clubman brings together economy and refinement. The pace of the Clubman is derived from its 1098 cc engine, which provides that extra bite in acceleration. The comfort of the Clubman comes from the all-round independent suspension which has been developed to give a smoother ride, and the luxuriously appointed interior.

The Clubman has cropped nylon seat wearing surfaces with rake-adjusting front seats, fitted carpets, leather bound steering wheel rim and padded fascia and parcel shelf. Face-level ventilation and opening rear quarter windows, with the fresh air heater, ensure your comfort in all weathers. Heated rear window, windscreen demisters and tinted glass let you know what's going on come rain or shine. There is also the extra cost option of

A worth-while Clubman Saloon safety feature is the extra-cost option of Denovo wheels and run-flat tyres—the remarkable tyres which give greatly increased safety in the event of a 'blowout' and let you carry on for up to 100 miles at speeds up to 50 m.p.h. You can then have the tyre repaired at an appointed Denovo Dealer.

If much of your driving is around town you may care to specify the extra-cost package of fully-automatic transmission, only available with 998 cc engine. Whether manual or automatic, you will appreciate the Clubman's attention to detail. Reliable, safe and comfortable, the Clubman looks after your every interest-right down to the lockable fuel filler cap fitted as standard. It's that kind of car.

MinipassionMini.com



4. Clubman Saloon

heated rear window.

Rear seating.

interior. 5. Electrically

6. Fitted carpet on door sills.













Specifications 850/1000

ENGINE: 4-cylinder, transverse, o.h.v. In unit, with clutch, gearbox and final drive

(850) Bore 2·478 in. (62·94 mm.); stroke 2·687 in. (68·25 mm.). Capacity 848 c.c. (51·74 cu. in.). S.U. type HS4 carburetter, 33 b.h.p. at 5,300 rev/min*; maximum torque 5·5 kgm at 2,500 rev/min*; compression ratio 8·3:1.

(1000) Bore 2·543 in. (64·58 mm.); stroke 3·0 in. (76·20 mm.). Capacity 998 c.c. (60·96 cu. in.). S.U. type HS4 carburetter, 39 b.h.p. at 4,750 rev/min*; maximum torque 7·12 kgm at 2,000 rev/min*; compression ratio 8·3:1.

CLUTCH: Diaphragm spring, 7-125 in. (0-18 m.) diameter. Hydraulically operated.

GEARBOX: 4-speed, all synchromesh on forward gears, remote control centre-floor gear change lever. Ratios: first 3-525; second 2-218; third 1-433; fourth 1-000: reverse 3-544: 1.

FINAL DRIVE: Front-wheel-drive with pre-lubricated universals on open shafts. Ratio: (850) 3-76:1, (1000) 3-44:1.

STEERING: Rack and pinion.

ROAD WHEELS: Pressed-steel disc. 145SR-10 radial-ply tyres.

BRAKES: Dual-line, diagonal split, hydraulically operated. 7 in. (0·18 m.) diameter drums all round. Two leading shoes at front, leading and trailing at rear.

SUSPENSION: Independent all round. Cone rubber springs and telescopic hydraulic dampers.

ELECTRICAL: 12-volt, 30 amp-hr. battery. Alternator. Multi-purpose lever on right-hand of steering-column controls horn, headlamp flasher, dip-switch and self-cancelling direction indicators. Lever on left-hand of steering-column controls electric windscreen washer and two-speed windscreen wipers with flick-wipe facility. Hazard warning lamps. Electrically heated rear window, fresh-air heater/demister and combined ignition/starter switch incorporating steering-column lock. (1000 only) Reversing lamps.

INSTRUMENTS: Speedometer. Fuel gauge. Warning lamps to show flashers/ hazard lamps working, headlamp high-beam, heated rear window on, brake line failure, low oil pressure (850 only) and no charge. (Separate instruments for oil pressure and water temperature on 1000 Saloon.)

COACHWORK: (850): 4-seater, 2-door Saloon of all-steel unitary construction. Wind-down door windows. Exterior mirror. Knit-backed expanded vinyl seat wearing surfaces. Handbrake grip. Vanity mirror in passenger's sun visor. Ticket pocket in driver's sun visor. Rubber floor mats. Factory fitted inertia reel front seat belts.

COACHWORK: (1000): 4-seater, 2-door Saloon of all-steel unitary construction. Wind-down door windows. Interior dipping rear-view mirror. Exterior mirror. Striped cropped nylon seat wearing surfaces. Rake-adjusting front seats. Handbrake grip. Vanity mirror in passenger's sun visor. Ticket pocket in driver's sun visor. Door pocket. Coachline. Face-level vents. Hinged rear quarter windows. Fitted floor carpet. Factory fitted inertia reel front seat belts.

OPTIONAL EXTRA: (1000 Saloon only): Automatic transmission.

EXPORT MARKETS: The specifications of these models are correct for the U.K. market at date of printing. Export specifications may differ to suit conditions and regulations of overseas territories. Please check details with your Dealer.

Clubman Saloon & Estate

ENGINE: 4-cylinder, transverse, o.h.v. In unit with clutch, gearbox and final drive. Bore 2-543 in. (64-58 mm.); stroke 3-296 in. (83-73 mm.). Capacity 1098 c.c. (67 cu. in.). S.U. type HS4 carburetter, 45 b.h.p. at 5,250 rev/min*; maximum torque 7-7 kgm at 2,700 rev/min*; compression ratio 8-5: 1.

CLUTCH: Diaphragm spring, 7·125 in. (0·18 m.) diameter. Hydraulically operated.

GEARBOX: 4-speed, all synchromesh on forward gears, remote control centrefloor gear change lever. Ratios: first 3-525; second 2-218; third 1-433; fourth 1-000; reverse 3-544: 1.

FINAL DRIVE: Front-wheel-drive with pre-lubricated universals on open shafts. Ratio 3:44:1.

STEERING: Rack and pinion. Leather bound steering wheel rim.

ROAD WHEELS: Pressed-steel disc with 145SR-10 radial-ply tyres.

BRAKES: Dual-line, diagonal split, hydraulically operated. 7 in. (0·18 m.) diameter drums all round. Two leading shoes at front, leading and trailing at rear.

SUSPENSION: Independent all round. Cone rubber springs and telescopic hydraulic dampers.

ELECTRICAL: 12-volt, 30 amp. hr. (Saloon), 36 amp. hr. (Estate) battery. Alternator. Multi-purpose lever on right-hand of steering-column controls horn, headlamp flasher, dip-switch and self-cancelling direction indicators. Lever on left-hand of steering-column controls electric windscreen washer and two-speed windscreen wipers with flick-wipe facility. Hazard warning lamps. Electrically heated rear window (Saloon only), fresh-air heater/demister and combined ignition/starter switch incorporating steering-column lock. (Saloon only) Reversing lamps.

INSTRUMENTS: Speedometer. Fuel and water temperature gauges. Warning lamps to show flashers/hazard lamps working, headlamp high-beam, heated rear window on (Saloon only), brake line failure, low oil pressure and no charge.

COACHWORK: (Saloon): 2-door, 4-seater saloon of all-steel unitary construction. Wind-down door windows. Hinged rear quarter windows. Interior dipping rear-view mirror. Exterior mirror. Cropped nylon seat. wearing surfaces. Rake-adjusting front seats. Fitted floor carpet. Handbrake grip. Vanity mirror in passenger's sun visor. Ticket pocket in driver's sun visor. Door pocket. Tinted glass. Lockable fuel filler cap. Coachline. Factory fitted inertia reel front seat belts. Wheel trims. Face-level vents.

COACHWORK: (Estate): 2-door, all-steel, dual-purpose vehicle of unitary construction. 4-seater with folding rear seat to provide extra load carrying capacity. Wind-down door windows. Sliding window each side of rear compartment. Interior dipping rear-view mirror. Twin exterior door mirrors. Cropped nylon seat wearing surfaces. Rake-adjusting front seats. Fitted floor carpet, except load compartment which has vinyl coated felt mat. Handbrake grip. Vanity mirror in passenger's sun visor. Ticket pocket in driver's sun visor. Door pocket. Tinted glass. Lockable fuel filler cap. Double line coach stripe. Factory fitted inertia reel front seat belts. Wheel trims. Face-level vents.

OPTIONAL EXTRAS: Automatic transmission with 998 cc engine. (Saloon only) Denovo wheels and tyres. (Saloon only) Metallic paint.

EXPORT MARKETS: The specifications of these models are correct for the U.K. market at date of printing. Export specifications may differ to suit conditions and regulations of overseas territories. Please check details with your Dealer.

1275 GT

ENGINE: 4-cylinder, transverse, o.h.v. In unit with clutch, gearbox and final drive. Bore 2-78 in. (70-61 mm.); stroke 3-20 in. (81-28 mm.). Capacity 1275 c.c. (77-8 cu. in.). S.U. type HS4 carburetter, 54 b.h.p. at 5,250 rev/min*; maximum torque 9-2 kgm at 2,500 rev/min*; compression ratio 8-8: 1.

CLUTCH: Diaphragm spring, 7-125 in. (0-18 m.) diameter. Hydraulically operated.

GEARBOX: 4-speed, all synchromesh on forward gears. Remote control centre-floor gear change lever. Ratios: first 3-330; second 2-094; third 1-353; top 1-000: reverse 3-347: 1.

FINAL DRIVE: Front-wheel-drive, with pre-lubricated universals on open shafts. Ratio: 3.44:1.

STEERING: Rack and pinion. Leather bound steering wheel rim.

ROAD WHEELS: Dunlop Denovo wheels with 155/65SR-310 tyres.

BRAKES: Dual-line, diagonal split, hydraulically operated. 8·4 in. (0·21 m.) diameter discs at front, 7 in. (0·18 m.) drums at rear.

SUSPENSION: Independent all round. Cone rubber springs and telescopic hydraulic dampers.

ELECTRICAL: 12-volt, 40 amp.-hr. battery. Alternator. Multi-purpose lever on right-hand of steering-column controls horn, headlamp flasher, dip-switch and self-cancelling direction indicators. Lever on left-hand of steering-column controls electric windscreen washer and two-speed windscreen wipers with flick-wipe facility. Hazard warning lamps. Reversing lamps. Electrically heated rear window, fresh-air heater/demister and combined ignition/starter switch incorporating steering-column lock.

INSTRUMENTS: Speedometer. Fuel and water temperature gauges. Revolution counter. Warning lamps to show flashers/hazard lamps working, headlamp high-beam, heated rear window on, brake line failure, low oil pressure and no charge.


COACHWORK: 2-door, 4-seater saloon of all steel unitary construction. Fitted floor carpet. Wind-down door windows. Hinged rear quarter windows. Interior dipping rear-view mirror. Twin exterior door mirrors. Striped cropped nylon seat wearing surfaces. Rake-adjusting front seats. Handbrake grip. Vanity mirror in passenger's sun visor. Ticket pocket in driver's sun visor. Door pocket. Tinted glass. Lockable fuel filler cap. Wheel trims. Triple line side stripe. Factory fitted inertia reel front seat belts. Face-level vents.


OPTIONAL EXTRA: Metallic paint.

EXPORT MARKETS: The specification of this model is correct for the U.K. market at date of printing. Export specifications may differ to suit conditions and regulations of overseas territories. Please check details with your Dealer.

Dimensions

850/1000







				in.	m.	
*Front seat cushion to roof		At		37.50	0.95	
*Rear seat cushion to roof		Bt		33-50	0.85	
*Front cushion depth		C		16-80	0.43	
*Rear cushion depth		D		16.25	0.41	
*Front squab height		E		17-90	0.46	
*Rear squab height		F		20.00	0.51	
*Height of front cushion		G		13.50	0.34	
*Height of rear cushion		H		13.50	0.34	
*Back of front squab to fr	ont of		∫ max.	11.50	0.29	
rear cushion		1	min.	7.50	0.19	
*Ctooring wheel to front or	-uah		∫ max.	16.50	0.42	
*Steering-wheel to front so	quab	J	min.	12.50	0.32	
*Steering-wheel to cushio	n	K		6.50	0.17	
*lan room front	3		∫ max.	44.00	1.12	
*Leg room—front	***	-	min.	41.00	1.04	
*1			∫ max.	44.50	1.13	
*Leg room—rear		М	min.	38.50	0.97	
Luggage boot height	5000	N	max.	16.00	0.41	
Luggage boot depth		0	max.	19-25	0.49	

***************				_		in.	m.
Luggage boot w				P	max.	38-00	0.96
*Width of front s	eat			Q1		20.00	0.51
*Overall width of	front	seats		Q2		44.50	1.13
*Width of rear cu	shion			R		41.00	1.04
Max. width betv	veen d	oor ca	sings	S		47.00	1.19
Width over front						3000000	0.0.0000
height			Linear	U		46-00	1.17
Width over rear			lder				
height		S. 2.		V		44.50	1.13
Wheelbase				w		80-16	2.04
Overall height				X		53-00	1.35
Overall width				Y		55-50	1.41
Overall length				Z		120-25	3.05
Door entry widt				AA		28-50	0.72
Kerbside weight	(app	rox.)		United to		1360 lb.	617 kg.

Clubman Estate





						in.	m.
	*Front seat cushion to r	oof		At		36.50	0.93
	*Rear seat cushion to re	oof		Bt		33.50	0.85
	*Front cushion depth			C		16.80	0.42
	*Rear cushion depth			D		16.30	0.41
	*Front squab height			E		17.90	0.45
	*Rear squab height			F		16-00	0.41
	*Height of front cushion	n		G		13-50	0.34
	*Height of rear cushion			H		14.50	0.37
	*Back of front squab to		nt of		max.	11.30	0.29
	rear cushion			1	min.	7.30	0.18
•					max.	16.50	0.42
	*Steering-wheel to from	t squ	ab	J	min.	12.50	0.32
	*Steering-wheel to cus	hion		K		6.50	0.17
					f max.	44.00	1.12
	*Leg room—front			L	min.	41.00	1.04
	22			7720-9	max.	44-50	1.13
	*Leg room—rear			M	min.	38-50	0.98
	Rear door height			N	max.	30-00	0.76
	Luggage boot depth			0	max.	29.50	0.75
	Luggage boot width			P	max.	49.50	1.26
	*Width of front seat			01		20.00	0.51


			in.	m.
*Overall width of front se	ats	Q2	44-50	1.13
*Width of rear cushion .		R	41-00	1.04
Max. width between doo	r casings	S	47.00	1.19
Width over front seat at s	houlder			
height		U	46.00	1.17
Width over rear seat at s				
hoight		V	45.00	1.14
1411		w	84-20	2.14
		X	53.50	1.36
		Y	55-50	1.41
-		Z	133-90	3.40
D		AA	28.50	0.72
		AC	33.50	0.85
Luggage floor length-se	at down	AD	47.50	1.21
Height rear floor to grou	nd	AE	18.00	0.46
Rear door width		AG	37.00	0.94
Kerbside weight (approx			1514 lb.	686-8 kg.


*Approximate measurements †With seats compressed

†With seats compressed

tWith seats compressed

Clubman Saloon & 1275 GT






*Front seat cushion to roof .. At 0.93 *Rear seat cushion to roof .. Bt 33.50 0.85 Front cushion depth . . . C
Rear cushion depth . . . D
Front squab height . . . E 16-80 0.42 16.30 0.41 0.45 *Rear squab height F 20.00 0.51 *Height of front cushion *Height of rear cushion ... 13.50 0.34 13-50 0.34 *Back of front squab to front of 0.29 ∫ max. 11.50 rear cushion 0.19 max. 16-50 0.42 *Steering-wheel to front squab.. J min. 12-50 0.32 *Steering-wheel to cushion .. K 6.50 0.17 1.12 *Leg room—front L min. 41.00 1.04 max. 44.50 1.13 *Leg room—rear min. 38-50 0.98 Luggage boot height N max. 16-00 0.41 Luggage boot depth O max. 19-30 0.49 Luggage boot width P max. 37-50 0.95

					in.	m.
*Width of front	seat			Q1	20.00	0.51
*Overall width of	of front	seats		Q2	44.50	1.13
*Width of rear of	ushion			R	41-00	1.04
Max. width bet	ween d	oor ca	sings	S	47-00	1.19
Width over from						
height				U	46.00	1-17
Width over rea	r seat a	t shou	ılder			
height				v	44-50	1.13
Wheelbase				w	80-20	2.04
Overall height	(Saloo	n)		X	53.00	1.35
Overall height	(1275	GT)		X	53-55	1.36
Overall width				Y	55-50	1-41
Overall length				Z	124-60	3.17
Door entry wid	lth			AA	28-50	0.72
Approx. kerbsi						
Saloon					1406 lb.	638 kg.
1275 GT		**	• •		1488 lb.	675 kg.
*Approximate	measure	ement				

One of the most comprehensive service schemes ever offered.

If you're thinking of buying a car take a good look round at what's being offered. Ever since the introduction of Supercover, everyone will be claiming more luxury, more miles per gallon and more extras. But you cannot afford to ignore what Supercover means to you.

1. Free 24 hour on-the-spot roadside assistance.



2. Free get-you-there relay recovery service.



3. No limit to mileage for first-year warranty.

No matter
how many miles
you do, your free
parts and labour
warranty will
cover you for a full
year. (And there's a
second year
Warranty, with or
without AA membership,
available at low cost. Your
Dealer has full details.)

4. A new 69 point check-out service, free before any car goes on the road.



PASSENGER CAR FUEL CONSUMPTION ORDER 1977

Fuel Consumption Tests

The results of the officially approved tests for this range of models in miles per gallon and litres per 100 kilometres are as follows:

	l		Constant Speed					
Model	194500	ban ving	56 mph (90 kph)		75 mph (120 kph)			
	mpg	L/100 km	mpg	L/100 km	mpg	L/100 km		
Mini 850 Saloon Man.	39-3	7.2	48-7	5.8	_	_		
Mini 1000 Saloon Man.	38-8	7.3	48-5	5.8	33.0	8.5		
Mini 1000 Saloon Auto.	40-2	7.0	38-9	7.3	_	-		
Mini Clubman Saloon Auto.	37.4	7-6	37-4	7.6	_	_		
Mini Clubman 1100 Saloon Man.	35-3	8-0	46.8	6-0	32-1	8.8		
Mini Clubman Estate Auto.	37.4	7.6	36-3	7.8	_	_		
Mini Clubman 1100 Estate Man.	34-8	8-1	45-4	6-2	33.7	8-4		
Mini 1275 GT Man.	34.7	8-1	46.0	6.1	33-3	8-5		

Important Note

The results given above do not express or imply any guarantee of the fuel consumption of any particular car. Tests are not made on each car and there are inevitable differences between individual cars of the same model. Furthermore fuel consumption will be affected by particular modifications, by the driver's style and road and traffic conditions and by the extent to which a particular car has been driven and its standard of maintenance.

Information as to the result of officially approved tests on all cars tested is available for inspection by customers on any premises where these cars are displayed. (Effective from the 1st April, 1978.)

IMPORTANT NOTICE

British Leyland UK Limited is constantly seeking ways to improve the specification, design and production of its vehicles and alterations take place continually. While every effort is made to produce up to date literature, this Brochure should not be regarded as an infallible guide to current specification, nor does it constitute an offer for the sale of any particular vehicle. Distributors and Dealers are not agents of British Leyland UK Limited and have absolutely no authority to bind British Leyland UK Limited by any express or implied undertaking or representation.



British Leyland UK Limited, Grosvenor House, Redditch, Worcs. B97 4DQ